


# Kodak K3ARDC Ni-MH Rechargeable Battery

Effective: April 23, 2009



Dimensions are in millimeters and include label.

**System:**

**Nickel-Metal Hydride battery**

**Designation:**

**ANSI 1.2H4, IEC HR03**

**Nominal Voltage:**

**1.2 Volts**

**Nominal Capacity:**

**900 mAh**

**Minimum Capacity:**

**800 mAh**

**Charging Condition:**

**90 mA for 16h**

**Max. Discharge:**

**1.6 A Continuous to 1.0 V**

**2.4 A Intermittent**

**Temperature Ranges:**

**Operating**

**0°C to +50°C**

**Storage**

**-20°C to +30°C**

**Charging Approx.**

**0°C to +40°C**

**Weight:**

**12.5 grams**

**Terminals:**

**Flat Contacts**

**Jacket:**

**PVC Label**


**Internal Impedance:**

**0.020 Ohms (typical)**

**Charging Cycles:**

**Up to 400.**

**Maximum life is achieved by shallow discharge and charge conditions.**



**Note:**

- 1) No added Mercury / 99.9999% Mercury Free — 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free —4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) Batteries are NOT subject to European RoHS regulations
- 7) MSDS sheets are available on the Kodak website.
- 8) Operating at extreme temperature will significantly affect service and cycle life.
- 9) For best performance after a long period of non-use, charge and discharge the battery several times.

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met by Eastman Kodak Company. Company reserves the right to change and improve product characteristics at any time.

For more information, contact Eastman Kodak Company, 343 State Street, Rochester NY 14650-0811, Phone 1-800-242-2424

[www.kodak.com/go/batteries](http://www.kodak.com/go/batteries)

© Eastman Kodak Company, 2009

Kodak is a trademark.

K3ARDC-900